

510 W Arizona Ave DeLand, FL 32720

Email info@ballfabrics.com | www.ballfabrics.com | Phone 386-740- 7212 · Toll Free 866-360-1008 | Fax 386-740- 7206

PrivaScreen® 90 Specifications

COLORS

RED Image: Constraint of the second of t		
WHITE TAN BLACK GREY BROWN ORANGE NAVY	RED	
TAN Image: Constraint of the second of t		
TAN Image: Constraint of the second of t		
TAN Image: Constraint of the second of t	· · · · · · — —	
BLACK GREY BROWN ORANGE NAVY	WHITE	
BLACK GREY BROWN ORANGE NAVY		
BLACK GREY BROWN ORANGE NAVY		
BLACK GREY BROWN ORANGE NAVY	ΤΔΝ	
GREY Image: Comparison of the second of th	.,	
GREY Image: Comparison of the second of th		
GREY Image: Comparison of the second of th		
GREY BROWN ORANGE NAVY	BLACK	n de la completa de la constante de la constant La dense de la constante de la c
GREY BROWN ORANGE NAVY		
BROWN ORANGE NAVY		
BROWN ORANGE NAVY	GREY	and the second
BROWN ORANGE NAVY		A GARGE
ORANGE NAVY		
ORANGE NAVY	BROWN	
ΝΑΥΥ		
ΝΑΥΥ		
ΝΑΥΥ		
	ONANGE	
		A CHARLES CHARLES AND
BLUE	NAVY	
	BLUE	
	-	
ROYAL	ROYAL	
BLUE	BLUE	
ODEEN COLORADOR	ODEEN	
GREEN	GREEN	

Warran<mark>ty 4</mark>Years

Our best selling privacy screen. Constructed with high density polyethylene for excellent outdoor longevity. It is also knitted, so if the material is cut or torn it will not unravel. Available in 3 different finishing options:

- **150' Rolls** – Extra polyethylene yarn is knitted into the top and bottom edges so PrivaScreen90 is ready to install right off the roll.

- **150' Plus Rolls** – Top and bottom edges are sewn with a double-stitch 3-ply hem and grommets every 12". The ends can be cut on site and folded over for reinforcement.

- Custom – All edges are sewn with a double- stitch, 3-ply hem and grommets every 12". Panels are custom cut to your specifications.

Material: High Density Knitted Polyethylene

Standard Heights: 3'8" (for 4' chain link) 5'8" (for 6' chain link) 7'8" (for 8' chain link)

Density: 90%

Weight: 5 oz/sq-yd (ASTM-D3776)

Tear Strength: Warp 51lbs/Fill 52lbs (ASTM-D 5587, Opt #1)

Breaking Strength: Warp 107lbs/Fill 125lbs (ASTM-D5034)

Bursting Strength: 202 psi (ASTM-D3786)

Thread: #135 Polyester

Hems: 3-ply reinforced with a polypropylene binding

Grommets: #2 brass grommets every 12" with Triple Grommeted Corners

Grommet Strip: **Standard on Hts Over 8'** #2 brass grommets every 24"

